

- 花纹关系的实验研究[J]. 橡胶工业, 2017, 64(11): 655-659.
- [3] 崔志博, 王友善, 吴健, 等. 接地特性对轮胎纯侧偏六分力影响的数值研究[J]. 橡胶工业, 2017, 64(11): 678-682.
- [4] Lee H, Taheri S. Intelligent Tires—A Review of Tire Characterization Literature[J]. IEEE Intelligent Transportation Systems Magazine, 2017, 9(2): 114-130.
- [5] Matsuzaki R, Todoroki A. Wireless Monitoring of Automobile Tires for Intelligent Tires[J]. Sensors, 2008, 8(12): 8123.
- [6] Tuononen A J, Matilainen M J. Real-time Estimation of Aquaplaning with an Optical Tyre Sensor. Proceedings of the Institution of Mechanical Engineers Part D[J]. Journal of Automobile Engineering, 2009, 223(10): 1263-1272.
- [7] Yilmazoglu O, Brandt M, Sigmund J, et al. Integrated InAs/GaSb 3D Magnetic Field Sensors for “The Intelligent Tire” [J]. Sensors & Actuators A: Physical, 2001, 94(1-2): 59-63.
- [8] Ryosuke Matsuzaki, Akira Todoroki, Hideo Kobayashi, et al. Passive Wireless Strain Monitoring of a Tire Using Capacitance and Electromagnetic Induction Change[J]. Advanced Composite Materials, 2003, 14(2): 147-164.
- [9] Pohl A, Steindl R, Reindl L. The “Intelligent Tire” Utilizing Passive SAW Sensors Measurement of Tire Friction[J]. IEEE Transactions on Instrumentation & Measurement, 1999, 48(6): 1041-1046.
- [10] Federico Cheli, Edoardo Sabbioni, Pesce M, et al. A methodology for Vehicle Sideslip Angle Identification: Comparison with Experimental Data[J]. Vehicle System Dynamics, 2007, 45(6): 549-563.
- [11] Braghin F, Brusarosco M, Cheli F, et al. Measurement of Contact Forces and Patch Features by Means of Accelerometers Fixed Inside the Tire to Improve Future Car Active Control[J]. Vehicle System Dynamics, 2006, 44: 3-13.
- [12] Savaresi S M, Tanelli M, Langthaler P, et al. New Regressors for the Direct Identification of Tire Deformation in Road Vehicles Via “In-Tire” Accelerometers[J]. IEEE Transactions on Control Systems Technology, 2008, 16(4): 769-780.
- [13] Sakaguchi K, Suzuki M, Matsubara T, et al. Optimal Tire Force Allocation by Means of Smart Tire Technology[J]. SAE International Journal of Passenger Cars—Mechanical Systems, 2013, 61(1): 163-176.
- [14] Christian Oertel, Wei Y T. Tyre Rolling Kinematics and Prediction of Tyre Forces and Moments: Part I: A Theory and Method[J]. Vehicle System Dynamics, 2012, 50(11): 1673-1687.
- [15] Wei Y T, Christian Oertel, Shen X L. Tyre Rolling Kinematics and Prediction of Tyre Forces and Moments: Part II: A Simulation and Experiment[J]. Vehicle System Dynamics, 2012, 50(11): 1689-1706.
- [16] Hong H N, Cesbron J, Anfosso Ledee F, et al. Dependence of the Contact Area on the Velocity of a Rolling Tire[J]. Journal of the Acoustical Society of America, 2009, 123(5): 3868.

收稿日期: 2018-10-11

Tire Vertical Force Estimation based on Smart Tire System

WANG Yan¹, LIN Bingqin^{1,2}, LIANG Guanqun¹, WEI Yintao¹

(1. Tsinghua University, Beijing 100084, China; 2. Qingdao University of Technology, Qingdao 266520, China)

Abstract: The hardware test system of smart tire was built by using the MEMS accelerometer, and the tire vertical force was predicted by the system. In order to obtain the data of smart tire sensor under various working conditions, and verify the prediction algorithm, the drum bench test and vehicle experiment were carried out respectively. The results showed that, the vertical force prediction algorithm based on smart tire had high accuracy, and could meet the requirements of engineering applications.

Key words: smart tire; vertical force; multi-sensor fusion; prediction algorithm

一种轮胎外观检测方法

由苏州光图智能科技有限公司申请的专利(公开号 CN 108982545A, 公开日期 2018-12-11)“一种轮胎外观检测方法”, 涉及的轮胎外观检测方法包括以下步骤: (1) 对待测轮胎进行拾取和固定; (2) 通过照相机对旋转的待测轮胎进行拍摄以获得花纹面图案或侧面图案; (3) 获取

照相机所拍摄到的花纹面图案和侧面图案, 并将其与预设的轮胎比对数据进行对比分析, 判断待检测轮胎是否存在缺陷。通过该方法可以实现对轮胎的自动化检测, 提高检测效率和检测准确性, 克服现有轮胎检测技术中重复操作、界定问题难度大, 速度慢, 效率低的缺陷。

(本刊编辑部 马 晓)