

Influence of Discharge Temperature of Single-step Mixing Process on the Properties of Tread Compound of TBR Tire

Tian Chuanhu, Liu Qiang, Li Wanshun, Li Qiang, Zhu Pingli, Cao Shuai
(Shandong Bayi Tire Manufacture Co., Ltd., Zaozhuang 277800, China)

Abstract: The influence of discharge temperature of single-step mixing process on the properties of the tread compound of TBR tire was studied. In the discharge temperature range of 145~165 °C, when the temperature increased, the hardness, modulus at 100% elongation, modulus at 300% elongation and tensile strength of the tread compound changed a little, the ratio of modulus at 300% elongation and modulus at 100% elongation increased, and the elastic modulus and loss factor were more affected. When the discharge temperature was selected at 165 °C, the heat build-up of the compound was low and the rolling resistance of the tire was low.

Keywords: single step mixing process; discharge temperature; modulus; elastic modulus; loss factor



信息·资讯

大陆集团扩建轮胎研发中心

日前,大陆集团斯洛伐克普霍夫轮胎厂的研发中心扩建项目竣工。大陆集团为该项目已拨款 940 万美元,包括购置轮胎耐久性能试验机 and 建设轮胎分析实验室等。该研发中心设备先进,拥有 53 间实验室和 10 个会议室,研发人员增加 15%。研发中心主要为普霍夫轮胎厂

提供支持。普霍夫轮胎厂的轿车轮胎和轻型载重轮胎的年产能可 1600 万条。大陆集团也投资 1.35 亿美元,使普霍夫轮胎厂的轻型载重轮胎年产能增大 40 万条,使轻型载重轮胎总年产能达到 300 万条。

西安

科腾公司推出氢化苯乙烯嵌段共聚物新产品

科腾(Kraton)高性能聚合物公司推出 Kraton MD6951 和 Kraton MD1648 两款新型氢化苯乙烯嵌段共聚物。Kraton MD6951 产品保持了 Kraton A 系列产品的稳定性、柔软性、相容性和易用性等特征,增强的极性使其能与热塑性聚氨酯、聚苯乙烯和聚苯醚等产品相容,主

要用于保护性薄膜和声音阻尼材料等。Kraton MD1648 产品是一款增强橡胶段苯乙烯嵌段共聚物,它具有极高的弹性、强度,且粘度低,有助于制备弹性和柔软性好的制品,可用于生产汽车零部件、胶带、粘合剂等。

崔小明